

USHA[®]
WATER SOLUTIONS

EXPERIENCE
WATER COMING TO LIFE
WITH
SUPERIOR TECHNOLOGY

PRESENTING
WATER COOLER & DISPENSER RANGE

USHA[®]



www.ushawatersolutions.com

<http://www.facebook.com/ushainternational>

<https://twitter.com/Ushalntl>

USHAcare[®]

Toll free

1800-1033-111

ushawatersolutions.com



LEADING THE PATH TO YOUR COMFORT AND SAFETY WITH STYLE

A trusted household consumer durables brand dedicated to providing the best-in-class experience to its consumers far and wide, USHA's new range of Water coolers and dispensers is exclusively designed to suit your everyday water needs without compromising on your safety.

Choose from our new range of Water coolers and Dispensers, now touchless to provide the safety of use and contactless dispensing at all times. The advanced technology features like digital temperature control and programmed water dispensing functions deem our models perfect for your modern office spaces without compromising on performance and style.

CONTENTS



USHA WATER COOLERS	4	SP 6080 GB	31
OUR TECHNOLOGY	6	SP 60120 G	32
SS 2020 BG	7	SP 80120	33
SS 2040 G	8	SP 80150	34
SS 2040 G/NC	9	SP 150150 G	35
SS 4080	10	SP 150150 RC	36
SS 4080 NC	11	SRA 400 R	37
SS 4080 MF	12	SP 170400 NC	38
SS 4080 TRI WATER	13	WATER DISPENSERS	40
SS 4080 SENSOR	14	SS 1515 FOUNTAIN	41
SS 6080 GB	15	LAGUNA FRESH FS SENSOR	42
SS 6080 GB SENSOR	16	LAGUNA FRESH FSCC	43
SS 60120 G	17	LAGUNA FRESH FS	44
SS 60120 NC	18	I SENSE	45
SS 80120	19	AQUAGENIE+ FSCC	46
SS 80120 NC	20	AQUAGENIE+ FS	47
SS 80150	21	INSTAFRESH FSCC (WHITE)	48
SS 150150 G	22	INSTAFRESH FS (WHITE)	49
SS 150150 RC	23	INSTAFRESH TT (WHITE)	50
SS 150150 G NC	24	INSTAFRESH FSCC (WINE RED)	51
SS170400NC	25	INSTAFRESH FS (WINE RED)	52
4080 VCM SENSOR	26	PRODUCT TECHNICAL	
VCM 4080	27	SPECIFICATIONS - WATER COOLERS	54
SP 2040 G	28	PRODUCT TECHNICAL	
SP 4040	29	SPECIFICATIONS - WATER DISPENSERS	58
SP 4080	30		

USHA WATER COOLERS

POWERED TO PERFORM.
MADE TOUGH TO OUTPERFORM.

Usha's range of water coolers is designed to deliver like no other. While their efficient design and rugged body gives them a long life, their low power consumption and fast cooling gives you a best-in-class experience, every time.



OUR TECHNOLOGY



SENSOR BASED DISPENSING

Sensor Based Touchless technology ensure safety by contactless dispensing at all time.



CONDENSER COIL TECHNOLOGY

Usha water coolers come with anti-corrosive grooved copper tubing and aluminium blue fin technology that provide faster cooling, making it an energy efficient solution.



ECO-FRIENDLY REFRIGERANT

Environment friendly non-CFC R-134a refrigerant provides safety and better performance.



HFC FOAMING TECHNOLOGY

Climate-friendly HFC Puf technology that eliminates the traditional refrigeration system and ensures environment safety.

SS 2020 BG

TOP IN PERFORMANCE AND LOOKS TOO

Ergonomically designed for greater safety and more operational convenience through its hybrid design, this water cooler is also environment friendly and boasts a longer product life, ensuring that you always have pure drinking water.



Comes with a reliable reciprocating compressor for longer product life



High-quality stainless steel tank and components for safe water



Specially designed float valves made of food-grade plastic



Adjustable pedestals made of highly non-corrosive and strong material

POWER CONSUMPTION | 390 W

REFRIGERANT | R-134A (NON CFC)

POWER SUPPLY | VOLTAGE: 230 V AC
FREQUENCY: 50 Hz
1 PHASE AC

RATE OF COOLING | 20 L / h

STORAGE CAPACITY | 20 L

NUMBER OF FAUCETS | 1

Actual faucet design may differ.

SS 2040 G

Ergonomically designed, this water cooler cools water faster while its superior grooved copper tubes and high-efficiency compressor consumes less power. Its steel body and condenser coil blue fin technology ensures a longer product life.



- Comes with a reliable reciprocating compressor for longer product life
- High-quality stainless steel tank and components for safe water
- Water inlet hosepipe and overflow pipes provided with the unit
- Specially designed float valves made of food-grade plastic
- Adjustable pedestals made of highly non-corrosive and strong material

	POWER CONSUMPTION	390 W
	REFRIGERANT	R-134A (NON CFC)
	POWER SUPPLY	Voltage: 230 V AC Frequency: 50 Hz 1 Phase AC

	RATE OF COOLING	20 L / h
	STORAGE CAPACITY	40 L
	NUMBER OF FAUCETS	1

Actual faucet design may differ.

SS 2040 G/NC

Ergonomically designed, this water cooler cools water faster while its superior grooved copper tubes and high-efficiency compressor consumes less power. Its steel body and condenser coil blue fin technology ensures a longer product life.



- Separate faucet for Normal water
- Comes with a reliable reciprocating compressor for longer product life
- High-quality stainless steel tank and components for safe water
- Water inlet hosepipe and overflow pipes provided with the unit
- Specially designed float valves made of food-grade plastic
- Adjustable pedestals made of highly non-corrosive and strong material

	POWER CONSUMPTION	390 W
	REFRIGERANT	R-134A (NON CFC)
	POWER SUPPLY	Voltage: 230 V AC Frequency: 50 Hz 1 Phase AC

	RATE OF COOLING	20 L / h
	STORAGE CAPACITY	40 L
	NUMBER OF FAUCETS	2

Actual faucet design may differ.

SS 4080

Ergonomically designed for greater safety and more operational convenience, this water cooler is also environment friendly and boasts a longer product life, ensuring that you always have pure drinking water.



- Comes with a reliable reciprocating compressor for longer product life
- High-quality stainless steel tank and components for safe water
- Water inlet hosepipe and overflow pipes provided with the unit
- Specially designed float valves made of food-grade plastic
- Adjustable pedestals made of highly non-corrosive and strong material

	POWER CONSUMPTION	450 W
	REFRIGERANT	R-134A (NON CFC)
	POWER SUPPLY	Voltage: 230 V AC Frequency: 50 Hz 1 Phase AC

	RATE OF COOLING	40 L / h
	STORAGE CAPACITY	80 L
	NUMBER OF FAUCETS	2

Actual faucet design may differ.

SS 4080 NC

Ergonomically designed, this water cooler cools water faster while its superior grooved copper tubes and high-efficiency compressor consumes less power. Its steel body and condenser coil blue fin technology ensures a longer product life.



- Separate faucet for Normal water
- Comes with a reliable reciprocating compressor for longer product life
- High-quality stainless steel tank and components for safe water
- Water inlet hosepipe and overflow pipes provided with the unit
- Specially designed float valves made of food-grade plastic
- Adjustable pedestals made of highly non-corrosive and strong material

	POWER CONSUMPTION	450 W
	REFRIGERANT	R-134A (NON CFC)
	POWER SUPPLY	Voltage: 230 V AC Frequency: 50 Hz 1 Phase AC

	RATE OF COOLING	40 L / h
	STORAGE CAPACITY	80 L
	NUMBER OF FAUCETS	2

Actual faucet design may differ.

SS 4080 MF

Ergonomically designed for greater safety and more operational convenience, this water cooler is also environment friendly and boasts a longer product life, ensuring that you always have pure drinking water.

NEW LAUNCH



- Triple face design with taps on three sides for convenience during rush hours
- Comes with a reliable reciprocating compressor for longer product life
- High-quality stainless steel tank and components for safe water
- Water inlet hosepipe and overflow pipes provided with the unit
- Specially designed float valves made of food-grade plastic
- Adjustable pedestals made of highly non-corrosive and strong material
- Faucets at varied heights to cater to all kinds of users, including kids

	POWER CONSUMPTION	450 W
	REFRIGERANT	R-134A (NON CFC)
	POWER SUPPLY	Voltage: 230 V AC Frequency: 50 Hz 1 Phase AC

	RATE OF COOLING	40 L / h
	STORAGE CAPACITY	80 L
	NUMBER OF FAUCETS	4

Actual faucet design may differ.

SS 4080 TRI WATER

SUPERIOR TECHNOLOGY FOR SUPERIOR EXPERIENCE

Triwater is a perfect solution for all your hydration needs. With three temperature options in one convenient unit, staying refreshed has never been easier providing you with Hot, Cold & Normal Water options.

NEW LAUNCH



- Hot water faucet with temperature upto 60° C
- Concealed heating tank With insulation
- Electrical shock protection
- Thermostat & thermal fuse for dual layer protection

	POWER CONSUMPTION	450 W 1000 W
	REFRIGERANT	R-134A (NON CFC)
	POWER SUPPLY	Voltage: 230 V AC Frequency: 50 Hz 1 Phase AC

	RATE OF COOLING & HEATING	40 L / h 20 L / h
	STORAGE CAPACITY	80 L 2 L
	NUMBER OF FAUCETS	3

Actual faucet design may differ.

SS 4080 SENSOR

Enjoy the convenience of faster cooling with this water cooler. a with superior grooved copper tubes, it comes with a high efficiency compressor that consumes less power while its steel body and condenser coil blue fin technology ensure a longer product life.



- Sensor based contactless dispensing
- Comes with a reliable reciprocating compressor for longer product life
- High-quality stainless steel tank and components for safe water
- Water inlet hosepipe and overflow pipes provided with the unit
- Specially designed float valves made of food-grade plastic
- Adjustable pedestals made of highly non-corrosive and strong material

POWER CONSUMPTION | 450 W

REFRIGERANT | R-134A (NON CFC)

POWER SUPPLY | Voltage: 230 V AC
Frequency: 50 Hz
1 Phase AC

RATE OF COOLING | 40 L / h

STORAGE CAPACITY | 80 L

NUMBER OF FAUCETS | 2

Actual faucet design may differ.

SS 6080 GB

Ergonomically designed for greater safety and more operational convenience, this water cooler is also environment friendly and boasts a longer product life, ensuring that you always have pure drinking water.



- Comes with a reliable reciprocating compressor for longer product life
- High-quality stainless steel tank and components for safe water
- Specially designed float valves made of food-grade plastic
- Adjustable pedestals made of highly non-corrosive and strong material

POWER CONSUMPTION | 775 W

REFRIGERANT | R-134A (NON CFC)

POWER SUPPLY | Voltage: 230 V AC
Frequency: 50 Hz
1 Phase AC

RATE OF COOLING | 60 L / h

STORAGE CAPACITY | 80 L

NUMBER OF FAUCETS | 2

Actual faucet design may differ.

SS 6080 GB SENSOR

Designed for faster cooling, this model has superior grooved copper tubes and a high-efficiency compressor that ensures less power consumption. The stainless steel body and blue fin condenser coil technology ensure a longer product life.



- Sensor based contactless dispensing
- Comes with a reliable reciprocating compressor for longer product life
- High-quality stainless steel tank and components for safe water
- Water inlet hosepipe and overflow pipes provided with the unit
- Specially designed float valves made of food-grade plastic
- Adjustable pedestals made of highly non-corrosive and strong material

	POWER CONSUMPTION	775 W
	REFRIGERANT	R-134A (NON CFC)
	POWER SUPPLY	Voltage: 230 V AC Frequency: 50 Hz 1 Phase AC

	RATE OF COOLING	60 L / h
	STORAGE CAPACITY	80 L
	NUMBER OF FAUCETS	2

Actual faucet design may differ.

SS 60120 G

Ergonomically designed for greater safety and more operational convenience, this water cooler is also environment friendly and boasts a longer product life, ensuring that you always have pure drinking water.



- Special anticorrosive blue fin condenser for power efficient cooling
- Comes with a reliable reciprocating compressor for longer product life
- High-quality stainless steel tank and components for safe water
- Water inlet hosepipe and overflow pipes provided with the unit
- Specially designed float valves made of food-grade plastic
- Adjustable pedestals made of highly non-corrosive and strong material

	POWER CONSUMPTION	775 W
	REFRIGERANT	R-134A (NON CFC)
	POWER SUPPLY	Voltage: 230 V AC Frequency: 50 Hz 1 Phase AC

	RATE OF COOLING	60 L / h
	STORAGE CAPACITY	120 L
	NUMBER OF FAUCETS	2

Actual faucet design may differ.

SS 60120 NC

Ergonomically designed, this water cooler cools water faster. Its superior grooved copper tubes and high-efficiency compressor consumes less power, while its stainless steel body and condenser coil blue fin technology gives it a longer product life.



- Separate faucet for Normal water
- Comes with a reliable reciprocating compressor for longer product life
- High-quality stainless steel tank and components for safe water
- Water inlet hosepipe and overflow pipes provided with the unit
- Specially designed float valves made of food-grade plastic
- Adjustable pedestals made of highly non-corrosive and strong material

	POWER CONSUMPTION	775 W
	REFRIGERANT	R-134A (NON CFC)
	POWER SUPPLY	Voltage: 230 V AC Frequency: 50 Hz 1 Phase AC

	RATE OF COOLING	60 L / h
	STORAGE CAPACITY	120 L
	NUMBER OF FAUCETS	3

Actual faucet design may differ.

SS 80120

Ergonomically designed for greater safety and more operational convenience, this water cooler is also environment friendly and boasts a longer product life, ensuring that you always have pure drinking water.



- Special anticorrosive blue fin condenser for power efficient cooling
- Comes with a reliable reciprocating compressor for longer product life
- High-quality stainless steel tank and components for safe water
- Water inlet hosepipe and overflow pipes provided with the unit
- Specially designed float valves made of food-grade plastic
- Adjustable pedestals made of highly non-corrosive and strong material

	POWER CONSUMPTION	775 W
	REFRIGERANT	R-134A (NON CFC)
	POWER SUPPLY	Voltage: 230 V AC Frequency: 50 Hz 1 Phase AC

	RATE OF COOLING	80 L / h
	STORAGE CAPACITY	120 L
	NUMBER OF FAUCETS	2

Actual faucet design may differ.

SS 80120 NC

Enjoy faster cooling, greater safety, and convenience with this ergonomically designed water cooler. Its superior grooved copper tubes and high-efficiency compressor consumes less power while its steel body and condenser coil blue fin technology ensure a longer product life.



- Separate faucet for Normal water
- Comes with a reliable reciprocating compressor for longer product life
- High-quality stainless steel tank and components for safe water
- Water inlet hosepipe and overflow pipes provided with the unit
- Specially designed float valves made of food-grade plastic
- Adjustable pedestals made of highly non-corrosive and strong material

	POWER CONSUMPTION	775 W
	REFRIGERANT	R-134A (NON CFC)
	POWER SUPPLY	Voltage: 230 V AC Frequency: 50 Hz 1 Phase AC

	RATE OF COOLING	80 L / h
	STORAGE CAPACITY	120 L
	NUMBER OF FAUCETS	3

Actual faucet design may differ.

SS 80150

Ergonomically designed for greater safety and more operational convenience, this water cooler is also environment friendly and boasts a longer product life, ensuring that you always have pure drinking water. Its steel body and condenser coil blue fin technology ensures a longer product life.



- Comes with a reliable reciprocating compressor for longer product life
- High-quality stainless steel tank and components for safe water
- Water inlet hosepipe and overflow pipes provided with the unit
- Specially designed float valves made of food-grade plastic
- Adjustable pedestals made of highly non-corrosive and strong material

	POWER CONSUMPTION	775 W
	REFRIGERANT	R-134A (NON CFC)
	POWER SUPPLY	Voltage: 230 V AC Frequency: 50 Hz 1 Phase AC

	RATE OF COOLING	80 L / h
	STORAGE CAPACITY	150 L
	NUMBER OF FAUCETS	2

Actual faucet design may differ.

SS 150150 G

Ergonomically designed for greater safety and operational convenience, this water cooler is environment friendly and boasts a longer product life so that you always have pure drinking water. Its steel body and condenser coil blue fin technology ensures a longer product life.



- Comes with a reliable reciprocating compressor for longer product life
- High-quality stainless steel tank and components for safe water
- Water inlet hosepipe and overflow pipes provided with the unit
- Specially designed float valves made of food-grade plastic
- Adjustable pedestals made of highly non-corrosive and strong material

POWER CONSUMPTION 1550 W	RATE OF COOLING 150 L / h
REFRIGERANT R-134A (NON CFC)	STORAGE CAPACITY 150 L
POWER SUPPLY Voltage: 230 V AC Frequency: 50 Hz 1 Phase AC	NUMBER OF FAUCETS 2

Actual faucet design may differ.

SS 150150 RC

Ergonomically designed for greater safety and more operational convenience, this water cooler is also environment friendly and boasts a longer product life, ensuring that you always have pure drinking water. Its steel body and condenser coil blue fin technology ensures a longer product life.



- Equipped with Rotary Compressor
- Comes with a reliable reciprocating compressor for longer product life
- High-quality stainless steel tank and components for safe water
- Water inlet hosepipe and overflow pipes provided with the unit
- Specially designed float valves made of food-grade plastic
- Adjustable pedestals made of highly non-corrosive and strong material

POWER CONSUMPTION 1350 W	RATE OF COOLING 150 L / h
REFRIGERANT R-22 (NON CFC)	STORAGE CAPACITY 150 L
POWER SUPPLY Voltage: 230 V AC Frequency: 50 Hz 1 Phase AC	NUMBER OF FAUCETS 2

Actual faucet design may differ.

SS 150150 G NC

Enjoy the convenience of faster cooling with this ergonomically designed water cooler. Its superior grooved copper tubes and high efficiency compressor consumes less power while its steel body and condenser coil blue fin technology ensures a longer product life.



- Separate faucet for Normal water
- Comes with a reliable reciprocating compressor for longer product life
- High-quality stainless steel tank and components for safe water
- Water inlet hosepipe and overflow pipes provided with the unit
- Specially designed float valves made of food-grade plastic
- Adjustable pedestals made of highly non-corrosive and strong material

	POWER CONSUMPTION	1550 W
	REFRIGERANT	R-134A (NON CFC)
	POWER SUPPLY	Voltage: 230 V AC Frequency: 50 Hz 1 Phase AC

	RATE OF COOLING	150 L / h
	STORAGE CAPACITY	150 L
	NUMBER OF FAUCETS	3

Actual faucet design may differ.

SS 170400 NC

Ergonomically designed for greater safety and operational convenience, this water cooler is environment friendly and boasts a longer product life so that you have pure drinking always water.



- Separate faucet for Normal water
- Comes with a reliable reciprocating compressor for longer product life
- High-quality stainless steel tank and components for safe water
- Water inlet hosepipe and overflow pipes provided with the unit
- Specially designed float valves made of food-grade plastic
- Adjustable pedestals made of highly non-corrosive and strong material

	POWER CONSUMPTION	1550 W
	REFRIGERANT	R-134A (NON CFC)
	POWER SUPPLY	Voltage: 230 V AC Frequency: 50 Hz 1 Phase AC

	RATE OF COOLING	170 L / h
	STORAGE CAPACITY	400 L
	NUMBER OF FAUCETS	4

Actual faucet design may differ.

4080 VCM SENSOR

TOUCHLESS DISPENSING. DESIGNED FOR SAFETY. STYLED FOR COMPLIMENTS.

Designed to ensure safe and contactless dispensing at all times, the new touchless VCM water cooler is environment friendly and consumes less power. Suited for a dash of colour to brighten up your space, the model comes with bright design aesthetics, food-grade stainless steel tank and chrome-plated brass faucets to ensure safe drinking water and a longer product life.



NEW LAUNCH

- Sensor based contactless dispensing
- Comes with a reliable reciprocating compressor for longer product life
- High-quality stainless steel tank and components for safe water
- Water inlet hosepipe and overflow pipes provided with the unit
- Specially designed float valves made of food-grade plastic
- Adjustable pedestals made of highly non-corrosive and strong material

	POWER CONSUMPTION	450 W
	REFRIGERANT	R-134A (NON CFC)
	POWER SUPPLY	Voltage: 230 V AC Frequency: 50 Hz 1 Phase AC

	RATE OF COOLING	40 L / h
	STORAGE CAPACITY	80 L
	NUMBER OF FAUCETS	2

Actual faucet design may differ.

VCM 4080

Designed to ensure safe and contactless dispensing at all times, the new touchless VCM water cooler is environment friendly and consumes less power. Suited for a dash of colour to brighten up your space, the model comes with bright design aesthetics, food-grade stainless steel tank and chrome-plated brass faucets to ensure safe drinking water and a longer product life. Its steel body and condenser coil blue fin technology ensures a longer product life.



NEW LAUNCH

- Comes with a reliable reciprocating compressor for longer product life
- High-quality stainless steel tank and components for safe water
- Water inlet hosepipe and overflow pipes provided with the unit
- Specially designed float valves made of food-grade plastic
- Adjustable pedestals made of highly non-corrosive and strong material

	POWER CONSUMPTION	450 W
	REFRIGERANT	R-134A (NON CFC)
	POWER SUPPLY	Voltage: 230 V AC Frequency: 50 Hz 1 Phase AC

	RATE OF COOLING	40 L / h
	STORAGE CAPACITY	80 L
	NUMBER OF FAUCETS	2

Actual faucet design may differ.

SP 2040 G

Enjoy the convenience of faster cooling with this water cooler. Equipped with superior grooved copper tubes, it comes with a high efficiency compressor that consumes less power while its steel body and condenser coil blue fin technology ensure a longer product life.



- Comes with a reliable reciprocating compressor for longer product life
- High-quality stainless steel tank and components for safe water
- Water inlet hosepipe and overflow pipes provided with the unit
- Specially designed float valves made of food-grade plastic
- Adjustable pedestals made of highly non-corrosive and strong material

	POWER CONSUMPTION	390 W
	REFRIGERANT	R-134A (NON CFC)
	POWER SUPPLY	Voltage: 230 V AC Frequency: 50 Hz 1 Phase AC

	RATE OF COOLING	20 L / h
	STORAGE CAPACITY	40 L
	NUMBER OF FAUCETS	1

Actual faucet design may differ.

SP 4040

Enjoy the convenience of faster cooling with this water cooler. Equipped with superior grooved copper tubes, it comes with a high efficiency compressor that consumes less power while its steel body and condenser coil blue fin technology ensure a longer product life.



- Comes with a reliable reciprocating compressor for longer product life
- High-quality stainless steel tank and components for safe water
- Water inlet hosepipe and overflow pipes provided with the unit
- Specially designed float valves made of food-grade plastic
- Adjustable pedestals made of highly non-corrosive and strong material

	POWER CONSUMPTION	450 W
	REFRIGERANT	R-134A (NON CFC)
	POWER SUPPLY	Voltage: 230 V AC Frequency: 50 Hz 1 Phase AC

	RATE OF COOLING	40 L / h
	STORAGE CAPACITY	40 L
	NUMBER OF FAUCETS	1

Actual faucet design may differ.

SP 4080

Designed for faster cooling, this model has superior grooved copper tubes and a high-efficiency compressor that ensures less power consumption. The stainless steel body and blue fin condenser coil technology ensure a longer product life.



- Comes with a reliable reciprocating compressor for longer product life
- High-quality stainless steel tank and components for safe water
- Water inlet hosepipe and overflow pipes provided with the unit
- Specially designed float valves made of food-grade plastic
- Adjustable pedestals made of highly non-corrosive and strong material

	POWER CONSUMPTION	450 W
	REFRIGERANT	R-134A (NON CFC)
	POWER SUPPLY	Voltage: 230 V AC Frequency: 50 Hz 1 Phase AC

	RATE OF COOLING	40 L / h
	STORAGE CAPACITY	80 L
	NUMBER OF FAUCETS	2

Actual faucet design may differ.

SP 6080 GB

Enjoy the convenience of faster cooling with this water cooler. Equipped with superior grooved copper tubes, it comes with a high efficiency compressor that consumes less power while its steel body and condenser coil blue fin technology ensure a longer product life.



- Comes with a reliable reciprocating compressor for longer product life
- High-quality stainless steel tank and components for safe water
- Specially designed float valves made of food-grade plastic
- Adjustable pedestals made of highly non-corrosive and strong material

	POWER CONSUMPTION	775 W
	REFRIGERANT	R-134A (NON CFC)
	POWER SUPPLY	Voltage: 230 V AC Frequency: 50 Hz 1 Phase AC

	RATE OF COOLING	60 L / h
	STORAGE CAPACITY	80 L
	NUMBER OF FAUCETS	2

Actual faucet design may differ.

SP 60120 G

Designed for faster cooling, this model has superior grooved copper tubes and a high-efficiency compressor that ensures less power consumption. The stainless steel body and blue fin condenser coil technology ensure a longer product life.



- Comes with a reliable reciprocating compressor for longer product life
- High-quality stainless steel tank and components for safe water
- Water inlet hosepipe and overflow pipes provided with the unit
- Specially designed float valves made of food-grade plastic
- Adjustable pedestals made of highly non-corrosive and strong material

	POWER CONSUMPTION	775 W
	REFRIGERANT	R-134A (NON CFC)
	POWER SUPPLY	Voltage: 230 V AC Frequency: 50 Hz 1 Phase AC

	RATE OF COOLING	60 L / h
	STORAGE CAPACITY	120 L
	NUMBER OF FAUCETS	2

Actual faucet design may differ.

SP 80120

Enjoy the convenience of faster cooling with this water cooler. Equipped with superior grooved copper tubes, it comes with a high efficiency compressor that consumes less power while its steel body and condenser coil blue fin technology ensure a longer product life.



- Comes with a reliable reciprocating compressor for longer product life
- High-quality stainless steel tank and components for safe water
- Water inlet hosepipe and overflow pipes provided with the unit
- Specially designed float valves made of food-grade plastic
- Adjustable pedestals made of highly non-corrosive and strong material

	POWER CONSUMPTION	775 W
	REFRIGERANT	R-134A (NON CFC)
	POWER SUPPLY	Voltage: 230 V AC Frequency: 50 Hz 1 Phase AC

	RATE OF COOLING	80 L / h
	STORAGE CAPACITY	120 L
	NUMBER OF FAUCETS	2

Actual faucet design may differ.

SP 80150

Enjoy the convenience of faster cooling with this water cooler. Equipped with superior grooved copper tubes, it comes with a high efficiency compressor that consumes less power while its steel body and condenser coil blue fin technology ensure a longer product life.



- Comes with a reliable reciprocating compressor for longer product life
- Specially designed float valves made of food-grade plastic
- High-quality stainless steel tank and components for safe water
- Water inlet hosepipe and overflow pipes provided with the unit

	POWER CONSUMPTION	775 W
	REFRIGERANT	R-134A (NON CFC)
	POWER SUPPLY	Voltage: 230 V AC Frequency: 50 Hz 1 Phase AC

	RATE OF COOLING	80 L / h
	STORAGE CAPACITY	150 L
	NUMBER OF FAUCETS	2

Actual faucet design may differ.

SP 150150 G

Designed to ensure safe and contactless dispensing at all times, the new touchless VCM water cooler is environment friendly and consumes less power. Suited for a dash of colour to brighten up your space, the model comes with bright design aesthetics, food-grade stainless steel tank and chrome-plated brass faucets to ensure safe drinking water and a longer product life.



- Comes with a reliable reciprocating compressor for longer product life
- High-quality stainless steel tank and components for safe water
- Water inlet hosepipe and overflow pipes provided with the unit
- Specially designed float valves made of food-grade plastic
- Adjustable pedestals made of highly non-corrosive and strong material

	POWER CONSUMPTION	1550 W
	REFRIGERANT	R-134A (NON CFC)
	POWER SUPPLY	Voltage: 230 V AC Frequency: 50 Hz 1 Phase AC

	RATE OF COOLING	150 L / h
	STORAGE CAPACITY	150 L
	NUMBER OF FAUCETS	2

Actual faucet design may differ.

SP 150150 RC

Enjoy the convenience of faster cooling with this water cooler. Equipped with superior grooved copper tubes, it comes with a high efficiency compressor that consumes less power while its steel body and condenser coil blue fin technology ensure a longer product life.



- Robustly built rotary compressor with R22 refrigerant
- Comes with a reliable reciprocating compressor for longer product life
- High-quality stainless steel tank and components for safe water
- Water inlet hosepipe and overflow pipes provided with the unit
- Specially designed float valves made of food-grade plastic
- Adjustable pedestals made of highly non-corrosive and strong material

	POWER CONSUMPTION	1350 W
	REFRIGERANT	R-22 (NON CFC)
	POWER SUPPLY	Voltage: 230 V AC Frequency: 50 Hz 1 Phase AC

	RATE OF COOLING	150 L / h
	STORAGE CAPACITY	150 L
	NUMBER OF FAUCETS	2

Actual faucet design may differ.

SRA 400 R

Enjoy faster cooling, greater safety and convenience with this ergonomically designed instant water cooler. Its superior grooved copper tubes and high efficiency compressor consumes less power while its steel body and condenser coil blue fin technology ensures a longer product life.



- Comes with a reliable reciprocating compressor for longer product life
- High-quality stainless steel tank and components for safe water
- Water inlet hosepipe and overflow pipes provided with the unit
- Specially designed float valves made of food-grade plastic
- Adjustable pedestals made of highly non-corrosive and strong material







	POWER CONSUMPTION	1550 W
	REFRIGERANT	R-134A (NON CFC)
	POWER SUPPLY	Voltage: 230 V AC Frequency: 50 Hz 1 Phase AC

	RATE OF COOLING	150 L / h
	STORAGE CAPACITY	NA
	NUMBER OF FAUCETS	NA

Actual faucet design may differ.

SP 170400 NC

Enjoy the convenience of faster cooling with this ergonomically designed water cooler. Its superior grooved copper tubes and high efficiency compressor consumes less power while its steel body and condenser coil blue fin technology ensures a longer product life.

-  Separate faucet for Normal water
-  Comes with a reliable reciprocating compressor for longer product life
-  High-quality stainless steel tank and components for safe water
-  Water inlet hosepipe and overflow pipes provided with the unit
-  Specially designed float valves made of food-grade plastic
-  Adjustable pedestals made of highly non-corrosive and strong material

 **POWER CONSUMPTION** | 1550 W

 **REFRIGERANT** | R-134A (NON CFC)

 **POWER SUPPLY** | Voltage: 230 V AC
Frequency: 50 Hz
1 Phase AC

 **RATE OF COOLING** | 170 L / h

 **STORAGE CAPACITY** | 400 L

 **NUMBER OF FAUCETS** | 4



Actual faucet design may differ.

WATER DISPENSERS

TECHNOLOGY YOU CAN TRUST.

Usha water dispensers are perfect choice for your office space, promising best in class cooling while consuming less power.



SS 1515 FOUNTAIN

STANDING TALL WITH FAST COOLING AND IN-BUILT POWER BACKUP

This premium water cooler model comes with a storage capacity of 15 L and a 30 minute power backup for continuous water supply, offering a best-in-class water cooling experience.



Swan neck for comfortable use



Inbuilt 30 mins power backup for continuous water supply during powercut



Compact design suitable for modern décor

	POWER CONSUMPTION	390 W
--	--------------------------	-------

	REFRIGERANT	R-134A (NON CFC)
--	--------------------	------------------

	POWER SUPPLY	Voltage: 230 V AC Frequency: 50 Hz 1 Phase AC
--	---------------------	---

	RATE OF COOLING	15 L/h
--	------------------------	--------

	STORAGE CAPACITY	15 L
--	-------------------------	------

	NUMBER OF FAUCETS	1
--	--------------------------	---

*Contactless dispensing only, the actual faucet design may differ.

LAGUNA FRESH FS SENSOR

Enjoy the convenience of faster cooling with this ergonomically designed water cooler. Its superior grooved copper tubes and high efficiency compressor consumes less power while its steel body and condenser coil blue fin technology ensures a longer product life.



- Sensor based contactless dispensing
- Comes with a reliable reciprocating compressor for longer product life
- High-quality stainless steel tank and components for safe water
- Specially designed float valves made of food-grade plastic
- Adjustable pedestals made of highly non-corrosive and strong material

POWER CONSUMPTION	<ul style="list-style-type: none"> ❄️ 100 W 🔥 500 W 	RATE OF COOLING	<ul style="list-style-type: none"> ❄️ 3 L/h 🔥 5 L/h
REFRIGERANT	R-134A (NON CFC)	STORAGE CAPACITY	<ul style="list-style-type: none"> ❄️ 3.5 L 🔥 0.9 L
POWER SUPPLY	Voltage: 230 V AC Frequency: 50 Hz 1 Phase AC	NUMBER OF FAUCETS	1

*Contactless dispensing only, the actual faucet design may differ.

LAGUNA FRESH FSCC

Enjoy faster cooling, greater safety and convenience with this ergonomically designed instant water cooler. Its superior grooved copper tubes and high efficiency compressor consumes less power while its steel body and condenser coil blue fin technology ensures a longer product life.



- 18 L cooling cabinet with temp. ≤ 14°C for storing beverages
- Comes with a reliable reciprocating compressor for longer product life
- High-quality stainless steel tank and components for safe water
- Specially designed float valves made of food-grade plastic
- Adjustable pedestals made of highly non-corrosive and strong material

POWER CONSUMPTION	<ul style="list-style-type: none"> ❄️ 100 W 🔥 500 W 	RATE OF COOLING	<ul style="list-style-type: none"> ❄️ 3 L/h 🔥 5 L/h
REFRIGERANT	R-134A (NON CFC)	STORAGE CAPACITY	<ul style="list-style-type: none"> ❄️ 3 L 🔥 0.9 L
POWER SUPPLY	Voltage: 230 V AC Frequency: 50 Hz 1 Phase AC	NUMBER OF FAUCETS	1

Actual faucet design may differ.

LAGUNA FRESH FS

Enjoy the convenience of faster cooling with this ergonomically designed water cooler. Its superior grooved copper tubes and high efficiency compressor consumes less power while its steel body and condenser coil blue fin technology ensures a longer product life.



- Single faucet dispensing for convenience
- Individual faucets for hot, normal and cold water
- Anti rodent power cord
- Child lock on hot water faucets
- CFC free eco-friendly R-134a refrigerant

POWER CONSUMPTION	100 W 500 W	RATE OF COOLING	3 L/h 5 L/h
REFRIGERANT	R-134A (NON CFC)	STORAGE CAPACITY	3 L 0.9 L
POWER SUPPLY	Voltage: 230 V AC Frequency: 50 Hz 1 Phase AC	NUMBER OF FAUCETS	1

Actual faucet design may differ.

I SENSE

Enjoy faster cooling, greater safety and convenience with this ergonomically designed instant water cooler. Its superior grooved copper tubes and high efficiency compressor consumes less power while its steel body and condenser coil blue fin technology ensures a longer product life.



- 3 m tall height dispensing to prevent backache problems
- Individual faucets for hot, normal and cold water
- Digital control water dispensing hot water : up to 85°C, cold water: up to 15°C
- Child lock on hot water faucets
- CFC free eco-friendly R-134a refrigerant

POWER CONSUMPTION	90 W 580 W	RATE OF COOLING	2.5 L/h 4 L/h
REFRIGERANT	R-134A (NON CFC)	STORAGE CAPACITY	3 L 1 L
POWER SUPPLY	Voltage: 230 V AC Frequency: 50 Hz 1 Phase AC	NUMBER OF FAUCETS	2

*Contactless dispensing only, the actual faucet design may differ.

AQUAGENIE+ FSCC

Enjoy the convenience of faster cooling with this ergonomically designed water cooler. Its superior grooved copper tubes and high efficiency compressor consumes less power while its steel body and condenser coil blue fin technology ensures a longer product life.



- 18 L Cooling cabinet with temp. $\leq 14^{\circ}\text{C}$ for storing beverages
- Compact and sleek design to fit into any setting
- Individual faucets for hot, normal and cold water
- Safety mesh for rodent control
- Child lock on hot water faucets
- CFC free eco-friendly R-134a refrigerant

POWER CONSUMPTION | 120 W 500 W

REFRIGERANT | R-134A (NON CFC)

POWER SUPPLY | Voltage: 230 V AC
Frequency: 50 Hz
1 Phase AC

RATE OF COOLING | 2.5 L/h 5 L/h

STORAGE CAPACITY | 3.2 L 1 L

NUMBER OF FAUCETS | 3

Actual faucet design may differ.

AQUAGENIE+ FS

Enjoy faster cooling, greater safety and convenience with this ergonomically designed instant water cooler. Its superior grooved copper tubes and high efficiency compressor consumes less power while its steel body and condenser coil blue fin technology ensures a longer product life.



- Compact and sleek design to fit into any setting
- Individual faucets for hot, normal and cold water
- Safety mesh for rodent control
- Child lock on hot water faucets
- CFC free eco-friendly R-134a refrigerant
- Also comes with a 18 L storage cabinet

POWER CONSUMPTION | 100 W 500 W

REFRIGERANT | R-134A (NON CFC)

POWER SUPPLY | Voltage: 230 V AC
Frequency: 50 Hz
1 Phase AC

RATE OF COOLING | 2.5 L/h 5 L/h

STORAGE CAPACITY | 3.2 L 1 L

NUMBER OF FAUCETS | 3

Actual faucet design may differ.

INSTAFRESH FSCC (WHITE)

Enjoy the convenience of faster cooling with this ergonomically designed water cooler. Its superior grooved copper tubes and high efficiency compressor consumes less power while its steel body and condenser coil blue fin technology ensures a longer product life.



- 18 L Cooling cabinet with temp. $\leq 14^{\circ}\text{C}$ for storing beverages
- Compact and sleek design to fit into any setting
- Designed for efficient cooling even in hot indian conditions
- Safety mesh for rodent control
- Child lock on hot water faucets
- CFC free eco-friendly R-134a refrigerant

POWER CONSUMPTION	100 W 500 W
REFRIGERANT	R-134A (NON CFC)
POWER SUPPLY	Voltage: 230 V AC Frequency: 50 Hz 1 Phase AC

RATE OF COOLING	3 L/h 5 L/h
STORAGE CAPACITY	3 L 1 L
NUMBER OF FAUCETS	3

Actual faucet design may differ.

INSTAFRESH FS (WHITE)

Enjoy faster cooling, greater safety and convenience with this ergonomically designed instant water cooler. Its superior grooved copper tubes and high efficiency compressor consumes less power while its steel body and condenser coil blue fin technology ensures a longer product life.



- Compact and sleek design to fit into any setting
- Individual faucets for hot, normal and cold water
- Safety mesh for rodent control
- Child lock on hot water faucets
- CFC free eco-friendly R-134a refrigerant

POWER CONSUMPTION	90 W 500 W
REFRIGERANT	R-134A (NON CFC)
POWER SUPPLY	Voltage: 230 V AC Frequency: 50 Hz 1 Phase AC

RATE OF COOLING	3 L/h 5 L/h
STORAGE CAPACITY	3 L 1 L
NUMBER OF FAUCETS	3

Actual faucet design may differ.

INSTAFRESH TT (WHITE)

Enjoy the convenience of faster cooling with this ergonomically designed water cooler. Its superior grooved copper tubes and high efficiency compressor consumes less power while its steel body and condenser coil blue fin technology ensures a longer product life.



- Individual faucets for hot, normal and cold water
- Compact and sleek design to fit into any setting
- Designed for efficient cooling even in hot indian conditions
- Safety mesh for rodent control
- Child lock on hot water faucets
- CFC free eco-friendly R-134a refrigerant

POWER CONSUMPTION	90 W 500 W
REFRIGERANT	R-134A (NON CFC)
POWER SUPPLY	Voltage: 230 V AC Frequency: 50 Hz 1 Phase AC

RATE OF COOLING	3 L/h 5 L/h
STORAGE CAPACITY	3 L 1 L
NUMBER OF FAUCETS	3

Actual faucet design may differ.

INSTAFRESH FSCC (WINE RED)

Enjoy faster cooling, greater safety and convenience with this ergonomically designed instant water cooler. Its superior grooved copper tubes and high efficiency compressor consumes less power while its steel body and condenser coil blue fin technology ensures a longer product life.



Also comes in black colour.

- 18 L Cooling cabinet with temp. $\leq 14^{\circ}\text{C}$ for storing beverages
- Compact and sleek design to fit into any setting
- Individual faucets for hot, normal and cold water
- Safety lock on hot water faucet
- CFC free eco-friendly R-134a refrigerant

POWER CONSUMPTION	100 W 500 W
REFRIGERANT	R-134A (NON CFC)
POWER SUPPLY	Voltage: 230 V AC Frequency: 50 Hz 1 Phase AC

RATE OF COOLING	3 L/h 5 L/h
STORAGE CAPACITY	3 L 1 L
NUMBER OF FAUCETS	3

Actual faucet design may differ.

INSTAFRESH FS (WINE RED)

Enjoy the convenience of faster cooling with this ergonomically designed water cooler. Its superior grooved copper tubes and high efficiency compressor consumes less power while its steel body and condenser coil blue fin technology ensures a longer product life.



Also comes in black colour.

- Compact and sleek design to fit into any setting
- Safety mesh for rodent control
- Individual faucets for hot, normal and cold water
- Safety lock on hot water faucet
- CFC free eco-friendly R-134a refrigerant

POWER CONSUMPTION | 90 W (cold) / 500 W (hot)

RATE OF COOLING | 3 L/h (cold) / 5 L/h (hot)

REFRIGERANT | R-134A (NON CFC)

STORAGE CAPACITY | 3 L (cold) / 1 L (hot)

POWER SUPPLY | Voltage: 230 V AC
Frequency: 50 Hz
1 Phase AC

NUMBER OF FAUCETS | 3

Actual faucet design may differ.

PRODUCT TECHNICAL SPECIFICATIONS

WATER COOLERS																	
PARTICULARS	Unit	SS 2040 G	SP 2040 G	SS 2040 G NC	SP 4040	SS 4080	SP 4080	SS 4080 NC	SS 6080 GB	SP 6080 GB	SS 60120 G	SP 60120 G	SS 80120	SP 80120	SS 80150	SP 80150	SS 150150 G
Cooling Capacity																	
At Rated Conditions	L/hr	20	20	20	40	40	40	40	60	60	60	60	80	80	80	80	150
At 10°C Temperature Drop	L/hr	35	35	35	65	65	65	65	100	100	100	100	130	130	130	130	245
Glasses/hr at Rated Condition	Nos	100	100	100	200	200	200	200	300	300	300	300	400	400	400	400	750
Storage Capacity	litres	40	40	40	40	80	80	80	80	80	120	120	120	120	150	150	150
Power Supply	230V ± 10%, 50Hz Single Phase AC																
Rated Current	Amp.	2	2	2	2.5	2.5	2.5	2.5	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	7.5
Power Input	Watt.	390	390	390	450	450	450	450	775	775	775	775	775	775	775	775	1550
Sheet Metal Outer Panels Material																	
Top Lid		SS-204 with Guard Film	PPGI with Guard Film (Horizon Blue)	SS-204 with Guard Film	PPGI with Guard Film (Horizon Blue)	SS-204 with Guard Film	PPGI with Guard Film (Horizon Blue)	SS-204 with Guard Film	SS-204 with Guard Film	PPGI with Guard Film (Horizon Blue)	SS-204 with Guard Film	PPGI with Guard Film (Horizon Blue)	SS-204 with Guard Film	PPGI with Guard Film (Horizon Blue)	SS-204 with Guard Film	PPGI with Guard Film (Horizon Blue)	SS-204 with Guard Film
Front Top		SS-204 with Guard Film	PPGI with Guard Film (Horizon Blue)	SS-204 with Guard Film	PPGI with Guard Film (Horizon Blue)	SS-204 with Guard Film	SS-204 with Guard Film	SS-204 with Guard Film	SS-204 with Guard Film	PPGI with Guard Film (Horizon Blue)	SS-204 with Guard Film	PPGI with Guard Film (Horizon Blue)	SS-204 with Guard Film	PPGI with Guard Film (Horizon Blue)	SS-204 with Guard Film	PPGI with Guard Film (Horizon Blue)	SS-204 with Guard Film
Front Bottom		SS-204 with Guard Film	SS-204 with Guard Film	SS-204 with Guard Film	SS-204 with Guard Film	SS-204 with Guard Film	SS-204 with Guard Film	SS-204 with Guard Film	SS-204 with Guard Film	SS-204 with Guard Film	SS-204 with Guard Film	SS-204 with Guard Film	SS-204 with Guard Film	SS-204 with Guard Film	SS-204 with Guard Film	SS-204 with Guard Film	SS-204 with Guard Film
Rear Top / Bottom		SS-204 with Guard Film	PPGI with Guard Film (Horizon Blue)	SS-204 with Guard Film	PPGI with Guard Film (Horizon Blue)	SS-204 with Guard Film	PPGI with Guard Film (Horizon Blue)	SS-204 with Guard Film	SS-204 with Guard Film	PPGI with Guard Film (Horizon Blue)	SS-204 with Guard Film	PPGI with Guard Film (Horizon Blue)	SS-204 with Guard Film	PPGI with Guard Film (Horizon Blue)	SS-204 with Guard Film	PPGI with Guard Film (Horizon Blue)	SS-204 with Guard Film
Side Panels		SS-204 with Guard Film	PPGI with Guard Film (Horizon Blue)	SS-204 with Guard Film	PPGI with Guard Film (Horizon Blue)	SS-204 with Guard Film	PPGI with Guard Film (Horizon Blue)	SS-204 with Guard Film	SS-204 with Guard Film	PPGI with Guard Film (Horizon Blue)	SS-204 with Guard Film	PPGI with Guard Film (Horizon Blue)	SS-204 with Guard Film	PPGI with Guard Film (Horizon Blue)	SS-204 with Guard Film	PPGI with Guard Film (Horizon Blue)	SS-204 with Guard Film
Base Plate		GPSP Powdercoated (1.4 mm Thickness)	GPSP Powdercoated (1.4 mm Thickness)	GPSP Powdercoated (1.4 mm Thickness)	GPSP Powdercoated (1.4 mm Thickness)	GPSP Powdercoated (1.4 mm Thickness)	GPSP Powdercoated (1.4 mm Thickness)	GPSP Powdercoated (1.4 mm Thickness)	GPSP Powdercoated (1.4 mm Thickness)	GPSP Powdercoated (1.4 mm Thickness)	GPSP Powdercoated (1.4 mm Thickness)	GPSP Powdercoated (1.4 mm Thickness)	GPSP Powdercoated (1.4 mm Thickness)	GPSP Powdercoated (1.4 mm Thickness)	GPSP Powdercoated (1.4 mm Thickness)	GPSP Powdercoated (1.4 mm Thickness)	GPSP Powdercoated (1.4 mm Thickness)
Key Part Details																	
Chiller Tank		Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)
Mask		ABS	ABS	ABS	ABS	HIPS	HIPS	HIPS	HIPS	HIPS	HIPS	HIPS	HIPS	HIPS	HIPS	HIPS	HIPS
Drip Tray		Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)
Faucet Material		Brass (Cr plated)	Brass (Cr plated)	Brass (Cr plated)	Brass (Cr plated)	Brass (Cr plated)	Brass (Cr plated)	Brass (Cr plated)	Brass (Cr plated)	Brass (Cr plated)	Brass (Cr plated)	Brass (Cr plated)	Brass (Cr plated)	Brass (Cr plated)	Brass (Cr plated)	Brass (Cr plated)	Brass (Cr plated)
No. of Faucets - Cold Water	Nos	1	1	1	1	2	2	1	2	2	2	2	2	2	2	2	2
No. of Faucets - Normal Water	Nos	-----	-----	1	-----	-----	-----	1	-----	-----	-----	-----	-----	-----	-----	-----	-----
No. of Faucets - Hot Water	Nos	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----
Condenser Tubing		Grooved copper with Aluminium Blue Fin	Grooved copper with Aluminium Blue Fin	Grooved copper with Aluminium Blue Fin	Grooved copper with Aluminium Blue Fin	Grooved copper with Aluminium Blue Fin	Grooved copper with Aluminium Blue Fin	Grooved copper with Aluminium Blue Fin	Grooved copper with Aluminium Blue Fin	Grooved copper with Aluminium Blue Fin	Grooved copper with Aluminium Blue Fin	Grooved copper with Aluminium Blue Fin	Grooved copper with Aluminium Blue Fin	Grooved copper with Aluminium Blue Fin	Grooved copper with Aluminium Blue Fin	Grooved copper with Aluminium Blue Fin	Grooved copper with Aluminium Blue Fin
Legs		PP (B120MA)	PP (B120MA)	PP (B120MA)	PP (B120MA)	PP (B120MA)	PP (B120MA)	PP (B120MA)	PP (B120MA)	PP (B120MA)	PP (B120MA)	PP (B120MA)	PP (B120MA)	PP (B120MA)	PP (B120MA)	PP (B120MA)	PP (B120MA)
Water Inlet Hose Pipe		Provided	Provided	Provided	Provided	Provided	Provided	Provided	---	---	Provided	Provided	Provided	Provided	Provided	Provided	Provided
Over Flow Pipe		Provided	Provided	Provided	Provided	Provided	Provided	Provided	---	---	Provided	Provided	Provided	Provided	Provided	Provided	Provided
Compressor/ Refrigerant		Recip. / R-134a	Recip. / R-134a	Recip. / R-134a	Recip. / R-134a	Recip. / R-134a	Recip. / R-134a	Recip. / R-134a	Recip. / R-134a	Recip. / R-134a	Recip. / R-134a	Recip. / R-134a	Recip. / R-134a	Recip. / R-134a	Recip. / R-134a	Recip. / R-134a	Recip. / R-134a
Net Weight (Excl. Packing)	Kg.	32	32	33	34.5	42	42	43	45	45	53	53	53	53	59	59	75
Unit Dimensions (W x D x H)	mm.	400 x 400 x 1200	400 x 400 x 1200	400 x 400 x 1210	400 x 400 x 1210	590 x 490 x 1200	590 x 490 x 1200	590 x 490 x 1200	590 x 490 x 1200	590 x 490 x 1200	700 x 550 x 1200	700 x 550 x 1200	700 x 550 x 1200	700 x 550 x 1200	700 X 550 X 1340	695 x 545 x 1340	700 X 550 X 1340

As we are constantly upgrading our product. All specifications, descriptions and illustrations are subject to change without any prior notification.

PRODUCT TECHNICAL SPECIFICATIONS

WATER COOLERS															
PARTICULARS	Unit	SP 150150 G	SS 150150RC	SP 150150RC	SS 170400 NC	SP 170400 NC	SS 2020 BG STORAGE CUM BUBBLE TOP	SRA 400R INSTANT TYPE	1515 ROUND SHAPE	VCM FRONT FACIA- 4080	4080 MULTI FAUCET	SS 4080 SENSOR	SS 4080 VCM SENSOR	SS 6080 GB SENSOR	SS 4080 HNC TRIWATER
Cooling Capacity															
At Rated Conditions	L/hr	150	150	150	170	170	20	150	15	40	40	40	40	60	40
At 10°C Temperature Drop	L/hr	245	245	245	280	280	35	245	25	65	65	65	65	100	65
Glasses/hr at Rated Condition	Nos	750	750	750	850	850	100	750	75	200	200	200	200	300	200
Storage Capacity	litres	150	150	150	400	400	20	---	15	80	80	80	80	80	80
Heating Capacity	litres	---	---	---	---	---	---	---	---	---	---	---	---	---	20
Power Supply															
230V ± 10%, 50Hz Single Phase AC															
Rated Current	Amp.	7.5	6.0	6.0	7.5	7.5	2	7.5	2	2.5	2.5	2.5	2.5	3.6	2.5
Power Input	Watt.	1550	1350	1350	1550	1550	390	1550	390	450	450	450	450	775	450/1000 (Cold/Hot)
Sheet Metal Outer Panels Material															
Top Lid		PPGI with Guard Film (Horizon Blue)	SS-204 with Guard Film	PPGI with Guard Film (Horizon Blue)	SS-204 with Guard Film	PPGI with Guard Film (Horizon Blue)	---	PPGI with Guard Film (Horizon Blue)	Outer body cyclinder body (SS304)	GPSP Powdercoated (Burgundy)	SS-204 with Guard Film	SS-204 with Guard Film	GPSP Powdercoated (Burgundy)	SS-204 with Guard Film	SS-204 with Guard Film
Front Top		PPGI with Guard Film (Horizon Blue)	SS-204 with Guard Film	PPGI with Guard Film (Horizon Blue)	SS-204 with Guard Film	PPGI with Guard Film (Horizon Blue)	SS-204 with Guard Film			VCM Sheet (Floral)	SS-204 with Guard Film	SS-204 with Guard Film	VCM Sheet	SS-204 with Guard Film	SS-204 with Guard Film
Front Bottom		SS-204 with Guard Film	SS-204 with Guard Film	SS-204 with Guard Film	SS-204 with Guard Film	SS-204 with Guard Film	SS-204 with Guard Film			VCM Sheet (Floral)	SS-204 with Guard Film	SS-204 with Guard Film	VCM Sheet	SS-204 with Guard Film	SS-204 with Guard Film
Rear Top / Bottom		PPGI with Guard Film (Horizon Blue)	SS-204 with Guard Film	PPGI with Guard Film (Horizon Blue)	SS-204 with Guard Film	PPGI with Guard Film (Horizon Blue)	SS-204 with Guard Film			GPSP Powdercoated (Burgundy)	SS-204 with Guard Film	SS-204 with Guard Film	GPSP Powdercoated (Burgundy)	SS-204 with Guard Film	SS-204 with Guard Film
Side Panels		PPGI with Guard Film (Horizon Blue)	SS-204 with Guard Film	PPGI with Guard Film (Horizon Blue)	SS-204 with Guard Film	PPGI with Guard Film (Horizon Blue)	SS-204 with Guard Film			GPSP Powdercoated (Burgundy)	SS-204 with Guard Film	SS-204 with Guard Film	GPSP Powdercoated (Burgundy)	SS-204 with Guard Film	SS-204 with Guard Film
Base Plate		GPSP Powdercoated (1.4 mm Thickness)	GPSP Powdercoated (1.4 mm Thickness)	GPSP Powdercoated (1.4 mm Thickness)	GPSP Powdercoated (1.4 mm Thickness)	GPSP Powdercoated (1.4 mm Thickness)	GPSP Powdercoated (1.4 mm Thickness)			GPSP Powdercoated (1.4 mm Thickness)	GPSP Powdercoated (1.4 mm Thickness)	GPSP Powdercoated (1.4 mm Thickness)	GPSP Powdercoated (1.4 mm Thickness)	GPSP Powdercoated (1.4 mm Thickness)	GPSP Powdercoated (1.4 mm Thickness)
Key Part Details															
Chiller Tank		Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	- NA -	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)
Mask		HIPS	HIPS	HIPS	Stainless Steel (SS 304)	Stainless Steel (SS 304)	ABS	- NA -	- NA -	HIPS	HIPS	HIPS	HIPS	HIPS	HIPS
Drip Tray		Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	- NA -	Stainless Steel (SS 304) Top Basin	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)	Stainless Steel (SS 304)
Faucet Material		Brass (Cr. plated)	Brass (Cr. plated)	Brass (Cr. plated)	Brass (Cr. plated)	Brass (Cr. plated)	Brass (Cr. plated)	- NA -	Brass (Cr. plated) Swan neck type	Brass (Cr. plated)	Brass (Cr. plated)	Touchless Sensor/ Brass (Cr. plated Faucet)	Touchless Sensor/ Brass (Cr. plated Faucet)	Touchless Sensor/ Brass (Cr. plated Faucet)	Brass (Cr. plated)
No. of Faucets - Cold Water	Nos	2	2	2	3	3	1	---	1	2	4	2	2	2	1
No. of Faucets - Normal Water	Nos	---	---	---	1	1	---	---	---	---	---	---	---	---	1
No. of Faucets - Hot Water	Nos	---	---	---	---	---	---	---	---	---	---	---	---	---	1
Condenser Tubing		Grooved copper with Aluminium Blue Fin	Grooved copper with Aluminium Blue Fin	Grooved copper with Aluminium Blue Fin	Grooved copper with Aluminium Blue Fin	Grooved copper with Aluminium Blue Fin	Grooved copper with Aluminium Blue Fin	Grooved copper with Aluminium Blue Fin	Grooved copper with Aluminium Blue Fin	Grooved copper with Aluminium Blue Fin	Grooved copper with Aluminium Blue Fin	Grooved copper with Aluminium Blue Fin	Grooved copper with Aluminium Blue Fin	Grooved copper with Aluminium Blue Fin	Grooved copper with Aluminium Blue Fin
Legs		PP (B120MA)	PP (B120MA)	PP (B120MA)	PP (B120MA)	PP (B120MA)	PP (B120MA)	PP (B120MA)	PP (B120MA)	PP (B120MA)	PP (B120MA)	PP (B120MA)	PP (B120MA)	PP (B120MA)	PP (B120MA)
Water Inlet Hose Pipe		Provided	Provided	Provided	Provided	Provided	---	---	Provided	Provided	Provided	Provided	Provided	Provided	Provided
Over Flow Pipe		Provided	Provided	Provided	Provided	Provided	---	---	Provided	Provided	Provided	Provided	Provided	Provided	Provided
Compressor / Refrigerant		Recip. / R-134a	Rotary / R-22	Rotary / R-22	Recip. / R-134a	Recip. / R-134a	Recip. / R-134a	Recip. / R-134a	Recip. / R-134a	Recip. / R-134a	Recip. / R-134a	Recip. / R-134a	Recip. / R-134a	Recip. / R-134a	Recip. / R-134a
Net Weight (Excl Packing)	Kg.	75	57	57	125	125	30	53	31	44	44	42	42	45	45
Unit Dimensions (W x D x H)	mm.	700 X 550 X 1340	700 X 550 X 1340	700 X 550 X 1340	1190 X 715 X 1440	1190 X 715 X 1440	370 x 370 x 980	630 x 340 x 1010	(W X H) Ø 362 x 1280	590 x 490 x 1200	590 x 490 x 1200	590 x 490 x 1200	590 x 490 x 1200	590 x 490 x 1200	590 x 490 x 1200

PRODUCT TECHNICAL SPECIFICATIONS

WATER DISPENSER														
PARTICULARS	Unit	I Sense	SS 1515 Fountain	Instafresh Sensor	Lagunafresh (FSCC)	Lagunafresh (FS)	Lagunafresh (Sensor)	Instafresh White / Wine Red / Jet Black (FSCC)	Instafresh White / Wine Red / Jet Black (FS)	Instafresh (TT)	Aquagenie+ (FSCC)	Aquagenie+ (FS)	Aquagenie+ (FSCC)	Aquagenie+ (TT)
Technical Specification														
Number of Faucet	Nos	2	1	3	1	1	1	3	3	3	3	3	3	3
Refrigerant	-	CFC Free eco-friendly R-134a	R-134a (Non CFC) Refrigerant	CFC Free eco-friendly R-134a Refrigerant	CFC Free eco-friendly R-134a Refrigerant	CFC Free eco-friendly R-134a Refrigerant	CFC Free eco-friendly R-134a Refrigerant	CFC Free eco-friendly R-134a Refrigerant	CFC Free eco-friendly R-134a Refrigerant	CFC Free eco-friendly R-134a Refrigerant	CFC Free eco-friendly R-134a Refrigerant	CFC Free eco-friendly R-134a Refrigerant	CFC Free eco-friendly R-134a Refrigerant	CFC Free eco-friendly R-134a Refrigerant
Power Supply	-	230V ± 10% , 50Hz Single Phase AC	230V ± 10% , 50Hz Single Phase AC	230V ± 10% , 50Hz Single Phase AC	230V ± 10% , 50Hz Single Phase AC	230V ± 10% , 50Hz Single Phase AC	230V ± 10% , 50Hz Single Phase AC	230V ± 10% , 50Hz Single Phase AC	230V ± 10% , 50Hz Single Phase AC	230V ± 10% , 50Hz Single Phase AC	230V ± 10% , 50Hz Single Phase AC	230V ± 10% , 50Hz Single Phase AC	230V ± 10% , 50Hz Single Phase AC	230V ± 10% , 50Hz Single Phase AC
Product Dim.	LxWxH	270 mm x 420 mm x 1.3 m	350 mm x 1.03 m (Dia x H)	31 cm x 31.5 cm x 93.4 cm	310 mm x 370 mm x 1.01 m	310 mm x 350 mm x 1.01 m	310 mm x 350 mm x 1.01 m	31 cm x 31.5 cm x 93.4 cm	31 cm x 31.5 cm x 93.4 cm	31.3 cm x 35 cm x 50.6 cm	38 cm x 32 cm x 1 m	38 cm x 32 cm x 1 m	38 cm x 32 cm x 1 m	38 cm x 32 cm x 51 cm
Net Weight	kg	14.5	--	12.1	17.8	14	14	14.3	12.1	9.95	18.4	16	17	12.6
Gross Weight	kg	17.3	-	14.18	19.85	16	16	16.7	14.18	11.45	20.7	18.2	19.5	14.1
Power Consumption	Watt.	90 W / 580 W	390 W	90 W, 500 W	100 W / 500 W	100 W / 500 W	100 W / 500 W	100 W / 500 W	90 W / 500 W	90 W / 500 W	120 W / 500 W	100 W / 500 W	100 W / 500 W	100 W / 500 W
Cooling	Watt.	90W	390 W	90W	100W	100W	100W	100 W	90W	90W	120 W	100W	100W	100W
Heating	Watt.	580W	-	500W	500W	500W	500W	500 W	500W	500W	500 W	500W	500W	500W
Rate of Cooling	L / h	2.5	15	3	3	3	3	3	3	3	2.5	2.5	2.5	2.5
Rate of Heating	L / h	4	-	5	5	5	5	5	5	5	5	5	5	5
Storage Capacity	L	3L , 1L	15L	3L , 1L	3L , 0.9L	3L , 0.9L	3L , 0.9L	3L , 1L	3L , 1L	3L , 1L	3.2L , 1L	3.2L , 1L	3.2L , 1L	3.2L , 1L
Cold	L	3L	15L	3L	3L	3	3L	3L	3L	3L	3.2L	3.2L	3.2L	3.2L
Hot	L	1L	-	1L	0.9L	0.9L	0.9L	1L	1L	1L	1L	1L	1L	1L
Key Features														
Key Features 1	1.3m Tall height for easy dispensing to prevent backache problems	Cooling and storage capacity of 15L	Sensor technology for contactless dispensing	Fridge Cabinet capacity 20L	---	Sensor-based water dispensing for Hot, Normal & Cold Water	18L Cooling cabinet with temp. upto 14°C for storing beverages	---	Compact Design suitable to place on table	18L Cooling cabinet with temp. upto 14°C for storing beverages	---	18L Storage cabinet	Compact Design suitable to place on table	
Key Features 2	Programmed water dispensing In 200 mL / 300 mL / 400 mL / 500 mL capacity for measuring everyday glass of health	Swan neck for comfortable use	Compact and sleek design suitable for office or household	Cooling capacity 3L /h < 15°C at 35°C ambient	Cooling capacity 3L /h < 15°C at 35°C ambient	Single faucet for Hot, Cold & Normal water dispensing	Compact and sleek design to fit into any setting	Compact and sleek design to fit into any setting	Compact and sleek design to fit into any setting	Compact and sleek design to fit into any setting	Compact and sleek design to fit into any setting	Compact and sleek design to fit into any setting	Compact and sleek design to fit into any setting	
Key Features 3	Digital control water dispensing hot water: up to 85°C, cold water: up to 15°C	Inbuilt 30mins power backup for continuous water supply	Individual faucets for hot, normal and cold water for ease of operation	Heating capacity 5 L /h, 85±5°C	Heating capacity 5 L /h, 85±5°C	Heating capacity 5 L /h, 85±5°C	Designed for efficient cooling even in hot indian conditions	Designed for efficient cooling even in hot indian conditions	Designed for efficient cooling even in hot indian conditions	Safety mesh for rodent control	Safety mesh for rodent control	Safety mesh for rodent control	Safety mesh for rodent control	
Key Features 4	Bottom loading water bottle compartment to avoid heavy weight lifting	Compact design suitable for modern décor	Anti-rust faucets	CFC Free eco-friendly R-134a Refrigerant	Single faucet for Hot, Cold & Normal water dispensing	Cooling capacity 3L /h < 15°C at 35°C ambient	Safety lock on hot water faucet	Safety lock on hot water faucet	Safety lock on hot water faucet	Safety lock on hot water faucet	Safety lock on hot water faucet	Safety lock on hot water faucet	Safety lock on hot water faucet	
Key Features 5	CFC Free eco-friendly R-134a Refrigerant	---	CFC Free eco-friendly R-134a Refrigerant	Single faucet for Hot, Cold & Normal water dispensing	CFC Free eco-friendly R-134a Refrigerant	CFC Free eco-friendly R-134a Refrigerant	CFC Free eco-friendly R-134a Refrigerant	CFC Free eco-friendly R-134a Refrigerant	CFC Free eco-friendly R-134a Refrigerant	CFC Free eco-friendly R-134a Refrigerant	CFC Free eco-friendly R-134a Refrigerant	CFC Free eco-friendly R-134a Refrigerant	CFC Free eco-friendly R-134a Refrigerant	
Key Features 6	---	---	---	Compact and Dual tone finish	Compact and Dual tone finish	Compact and Dual tone finish	---	---	---	---	---	---	---	

As we are constantly upgrading our product. All specifications, descriptions and illustrations are subject to change without any prior notification.

